

TRACTOR HYDRAULIC FLUID

TRACTOR HYDRAULIC FLUID is a premium, exceptional high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

TRACTOR HYDRAULIC FLUID meets the following specifications: **JOHN DEERE** J14B/C, J20A/B, J20C (HYGARD), J21A, JD 303 FLUID; **FORD NEW HOLLAND** M2C41-B, M2C48-B, M2C53-B, M2C86-B/C, M2C134-A/B/C/D, FNHA-2-C-201; **MASSEY FERGUSON** M-110, M-11271/B, M-1129A, M-1135, M-1141 (PERMATRAN III); **CASE** JIC 143, JIC 144, MS-120/JIC 185, MS-1205, MS-1206 (PTF), MS-1207 (HY-TRANS PLUS), MS-1209 (HY-TRANS ULTRA), MS-1210/JIC 145 (TCH FLUID); **WHITE FARM EQUIPMENT** Q-1705, Q-1722, Q-1766B, Q-1802 (TYPE 55 FLUID), Q-1826 (FTF); **AGCO** POWER FLUID 821XL, PF 821; **ALLISON** TYPE C-4. C-3; **CATERPILLAR** TO-2; **HESSTON FIAT** AF-87; **KUBOTA** UDT; **MINNEAPOLIS-MOLINE** 35154, 35202, 35301; **VICKERS** M-2950-S, 1-288-2; **SUNDSTRAND** HYDROSTATIC TRANSMISSION FLUID.

TYPICAL PROPERTIES

Product Code 441

Property	
Viscosity, cSt @ 40°C	59.5
Viscosity, cSt @ 100°C	9.25
Viscosity, cP @ -20°C	4,500
Viscosity, cP @ -35°C	49,000
Viscosity Index	150
Pour Point, °F	-44
Flash Point, °F	432
Sulfated Ash, wt%	1.48
Total Base Number	10.1
Zinc, wt%	0.157